



CAT5 Transmitter/Receiver (TTY115 + TRY315)



Qik Install pack is a twisted-pair transmitter and receiver pair with all necessary accessories like 5-ft input cable and a 50-ft CAT5e cable.

TTY115

Universal Transmitter for VGA Computer Video.
 TTY115 is a twisted-pair CAT5 Computer video transmitter. It encodes Computer video signals and transmits them over twisted-pair CAT5 cable at a distance up to 1000-ft. It is powered by the included AC adapter.

Key features:

- ⚡ Transmit (or receive) Computer video (VGA-UXGA) over a single twisted-pair CAT5 cable
- ⚡ Media distribution of VGA Computer video over a single twisted-pair CAT5 cable
- ⚡ Compact design easy to mount
- ⚡ Reduced cost and easy installation with use of standard, inexpensive, and flexible twisted-pair cabling.
- ⚡ Transmits signal up to 1000-ft away at UXGA (1600x1200) resolution
- ⚡ Ground Loop Protection

Front Panel Diagram



Back Panel Diagram



Specifications:

- Input** : 1x Computer Video on HD-15 F connector
- Output** : 1x Computer Video on HD-15 F connector 1x Computer Video on RJ45 connector
- Signal** : Standard Computer, RGBHV, or YPbPr Component Video
- Transmission Distance** : Up to 1000-ft receivers feature skew ompensation@ UXGA (1600x1200)
- Size-Weight** : 3.0" W x 3.9"D x 1.2" H, 0.5 lbs.
- Power** : Included AC power adapter, DC 5V from 110V input
- Expansion** : Cascadable
- Cable Compatibility** : CAT5e, Low-skew, CAT6, CAT5
- Approval** : CE/UL/FCC part 15 Class A
- Included Accessories** : AC power adapter

TRY315

VGA Computer Video Receiver up to 500-ft.
 TRY315 is a twisted-pair CAT5 computer video receiver. It decodes computer video signals received over twisted-pair cables from a distance of up to 1000-ft at UXGA (1600x1200) resolution. It features equalization and gain compensation for long cable runs. Simply plug-in input signal cable through RJ-45 plug and receive output video through HD-15 connector.

Key features:

- ⚡ Transmit (or receive) Computer video (VGA-UXGA) over a single twisted-pair CAT5 cable.
- ⚡ Media distribution of VGA Computer video over a single twisted-pair CAT5 cable.
- ⚡ Compact design easy to mount to display.
- ⚡ Reduced cost and easy installation with use of standard, inexpensive, and flexible twisted-pair cabling.
- ⚡ Receiver can be located up to 1000-ft away.
- ⚡ Equalization and gain compensation.
- ⚡ Compatible with Line Level Digital Stereo Audio Signals.

Front Panel Diagram



Back Panel Diagram



Specifications:

- Input** : 1x Computer Video on RJ45 connector.
- Output** : 1x Computer Video on HD-15 F connector.
- Signal** : Standard Computer, RGBHV, or YPbPr Component Video.
- Transmission Distance** : Up to 1000-ft receivers feature skew ompensation@ UXGA (1600x1200)
- Size-Weight** : 3.0" W x 3.9"D x 1.2" H, 0.5 lbs.
- Power** : Included AC power adapter, DC 5V from 110V input.
- Compatibility** : CAT5e, Low-skew, CAT6, CAT5
- Cable** : CE/UL/FCC part 15 Class A
- Approval** : CE/UL/FCC part 15 Class A

